SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: LEUBIT® Primer (10 Liter Kanister)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation: Coating compound/ Surface coating/ paint
- · Uses advised against: No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BVH

BITUMEN Vertrieb und Handel GmbH

Aue-Park-Allee 7 06237 Leuna

Tel.: +49 (0)346 38 3603-0 Fax: +49 (0)346 38 3603-29 Email: info@bvh-bitumen.de

• 1.4 Emergency telephone number: Tel.: +49 (0)361 730730, 24h (Erfurt)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aguatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms









GHS02 GHS07 GHS08 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C9, aromatics

· Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

(Contd. on page 2)

Trade name: LEUBIT® Primer (10 Liter Kanister)

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not determined.
- · vPvB: Not determined.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Dangerous components:		
	· · / · · · · · · · · · · · · · · · · · · ·	50-60%
Reg.nr.: 01-2119455851-35-XXXX	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Take affected persons out of danger area and lay down.

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- · After inhalation: Supply fresh air.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Remove contact lenses, if present and easy to do. Continue rinsing.
- After swallowing:

Rinse out mouth and then drink plenty of water.

Do NOT induce vomiting.

Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

CO₂, sand, extinguishing powder. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

· For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide

Carbon dioxide

- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.

(Contd. on page 3)

Trade name: LEUBIT® Primer (10 Liter Kanister)

(Contd. of page 2)

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Particular danger of slipping on leaked/spilled product.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs				
Hydrocar	Hydrocarbons, C9, aromatics			
Oral	DNEL(long/systemic)	11 mg/kg bw/day (Consumer)		
Dermal	DNEL(long/systemic)	11 mg/kg bw/day (Consumer)		
		25 mg/kg bw/day (Workers (Industrial/Professional))		
Inhalative	DNEL(long/systemic)	32 mg/m3 (Consumer)		
		150 mg/m3 (Workers (Industrial/Professional))		

Trade name: LEUBIT® Primer (10 Liter Kanister)

(Contd. of page 3)

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter Typ A (EN 14387)

Protection of hands:



Protective gloves

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

Nitrile rubber, NBR

PVC gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Colour:
Black
Odour:
Solvent-like
Odour threshold:
Not determined.

pH-value:
Not determined.

· Change in condition

Melting point/freezing point: Not determined. Initial boiling point and boiling range: Not determined.

· Flash point: > 23 °C

· Flammability (solid, gas): Not applicable.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: LEUBIT® Primer (10 Liter Kanister)

(Contd. of page 4)

	(Contd. of page 4)
· Ignition temperature:	ca. 220 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
· Explosion limits:	
Lower:	0.80 Vol %
Upper:	6.40 Vol %
Oxidising properties	No
· Vapour pressure:	Not determined.
Density at 20 °C:	0.93 g/mL
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Insoluble.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 23 °C:	≥ 15 s (DIN ISO 2431, 4 mm))
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability No decomposition if used and stored according to specifications.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Keep away from heat and direct sunlight.
- · 10.5 Incompatible materials: Strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
Hydrocar	Hydrocarbons, C9, aromatics		
Oral	LD50	3492 mg/kg (Rat)	
Dermal	LD50	> 3160 mg/kg (Rabbit) (OECD Guideline 402)	
Inhalative	LC50 (4h)	> 6.193 mg/L (Rat) (OECD Guideline 403, inhalation:vapour)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date: 12.05.2017 Version No: 1 Revision: 12.05.2017

Trade name: LEUBIT® Primer (10 Liter Kanister)

(Contd. of page 5)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
Hydrocarbons, C9, aromatics		
LC50 (96h)	9.2 mg/L (Fish) (OECD Guideline 203, Oncorhynchus mykiss) semi-static Water Accommodated Fractions (WAFs)	
ErC50 (72h) (static)	2.9 mg/L (Algae) (OECD Guideline 201,Pseudokirchneriella subcapitata) Water Accommodated Fractions (WAFs)	
EC50 (48h) (static)	3.2 mg/L (Daphnia) (OECD Guideline 202, Daphnia magna) Water Accommodated Fractions (WAFs)	
EC50 (static)	> 99 mg/L (Bacteria) (OECD Guideline 209, activated sludge) 10 min	
NOEC (static)	> 99 mg/L (Bacteria) (OECD Guideline 209, activated sludge) 10 min	
NOEL (21d)	2.144 mg/L (Daphnia) (QSAR, Daphnia magna)	
· 12.2 Persistence and degradability		
Hydrocarbons, C9, aromatics > 60 % @ 28d (OECD Guideline 301 F)		

Hydrocarbons, C9, aromatics > 60 % @ 28d (OECD Guideline 301 F)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · European waste catalogue

13 02 08* other engine, gear and lubricating oils

- Uncleaned packaging
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1139
· 14.2 UN proper shipping name	
· ADR/RID/ADN	1139 COATING SOLUTION, ENVIRONMENTALLY HAZARDOUS

Trade name: LEUBIT® Primer (10 Liter Kanister)

(Contd. of page 6)

	(Contd. of page 6)
· IMDG	COATING SOLUTION (Hydrocarbons, C9, aromatics, 1,2,4-trimethylbenzene), MARINE POLLUTANT
· IATA	COATING SOLUTION
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN, IMDG	
Class	3 Flammable liquids.
· Label	3
·IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: Hydrocarbons, C9, aromatics Symbol (fish and tree)
Special marking (ADR/RID/ADN):	Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> F
· 14.7 Transport in bulk according to Anne	
MARPOL73/78 and the IBC Code:	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Tunnel restriction code	D/E
· UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 5

(Contd. on page 8)

Printing date: 12.05.2017 Version No: 1 Revision: 12.05.2017

Trade name: LEUBIT® Primer (10 Liter Kanister)

(Contd. of page 7)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS:

BVH

BITUMEN Vertrieb und Handel GmbH

Aue-Park-Allee 7

D-06237 Leuna

Abbreviations and acronyms:

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals MARPOL: (from Marine Pollutant) International Convention for the Prevention of Marine Pollution from Ships

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

UN: United Nations (also UNO: United Nations Organization)

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

ASTM: American Society for Testing and Materials

WAF: Water Accommodated Fraction

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GB —