

LEUBIT®

56

primer plus

Technical data sheet

primer plus

for use before applying LEUBIT® HVM type N2

- LEUBIT® primer plus is a bitumen primer that contains solvents.
- This product was specifically developed for use before applying LEUBIT® HVM type N2.
- LEUBIT® primer plus penetrates effectively into the substrate, binds dust, cures quickly, and ensures a stable bond between joint edges and the compound to be applied.

Packaging



10 l bucket

36 buckets per pallet

Application areas

- LEUBIT® primer plus is ideal for priming surfaces and improving adhesion with LEUBIT® HVM type N2.
- LEUBIT® primer plus adheres to virtually any substrate used in construction, especially concrete and asphalt.
- For use in commercial applications only.

External conditions and application

- Clean the damaged area using a sweeper or compressed air before beginning repair work. The surface should be dry and free of dirt or other contaminants.
- Store the product and allow it to reach room temperature before application.
- Apply LEUBIT® primer plus onto the substrate evenly using a brush or roller. We recommend applying the product onto a strip of around a centimetre in width either side of the damaged area on the roadway first.
- Do not start on any subsequent work until after the primer has completely cured.
- The primed surfaces should not smudge when wiped by your finger.

Storage and storage life

- Store in a dry place protected from sunlight at more than 50°C
- Protect from frost
- Storage life at least 12 months

Disposal

- Always dispose of empty canisters and residual content according to your local, regional, national or international regulations.

Composition

- Bitumen blend containing solvents
- Solvent: toluene (<42%)